



HC140

SPECIFICATIONS

BATTERY DESIGN

- Absorbent glass mat (AGM) technology
- 12V battery VRLA
- Can be mounted in any orientation except inverted.
- US DOT and IATA certified non-spillable
- Sealed Construction (Non-Spillable Battery)
- Can be choose to fitted with TP brass automotive terminal
- Long Service Life
- Shipped fully charged - just install and go!

PERFORMANCE FEATURES

- PHCA: 2400A at 80°F (27°C) for 5 seconds
- PCCA: 1500A at 0°F (-18°C) for 5 seconds
- CCA: 1210A at 0°F (-18°C)
- CA/MCA: 1505A at 32°F (0°C)
- HCA: 1750A at 80°F (27°C)
- Reserve capacity: 321 minutes
- Short circuit current: 5000A
- Operation temperature range: -5°F (-15°C) to 122°F (50°C)

Nominal Dimensions

Length		Width		Height		Total Height		Weight	
mm	in	mm	in	mm	in	mm	in	kg	pound
327	12.87	182	7.17	269	10.59	273	10.75	44.2	97.44

HIGH RATE DISCHARGE AT 77°F (25°C)

5 sec.	10 sec.	20 sec.	30 sec.
2400A	2155A	1880A	1750A

EXTENDED DISCHARGE AT 77°F (25°C) TO 10.02V

5min	15min	1hr	3hr	5hr	10hr	20hr
461A	237A	85A	36.5A	24A	13.4A	7.20A

PHYSICAL CHARACTERISTICS

