



## DC160-12

**160AH@20HR**

**12-Volt**

**DEEP CYCLE**

**Maintenance-Free  
Sealed AGM Battery**




Nominal Specifications			
Battery Model	DC160-12	Rated Capacity	160AH/20HR
Mechanical Specifications			
Group Size	N/A		
Overall Height (H)	241±2mm	9.49"	
Container Height (h)	241±2mm	9.49"	
Length	484±2mm	19.06"	
Width	171±2mm	6.73"	
Weight	Approx.47kg	103.62lbs.	
Terminal Type	M8- Button Terminal		
Terminal Torque	9.6-10.7 N.m		
Container Material	ABS: Standard (UL 94-HB)		

Electrical Specifications	
C100	176AH
C20	160AH
C10	142AH
C5	130AH
CCA	910A
CA or MCA	1070A
HPCA	1270A
Max. Discharge Current	1600A (5s)
Internal Resistance	2.8mΩ
Reserve Capacity	
Reserve @25 AMPS	300Minutes
Reserve @75 AMPS	82Minutes


Temperature Range Specifications	
Operating Temperature Range	Discharge : -15°C ~+ 50°C (5°F ~122°F)
	Charge: -15°C ~ +40°C (5°F ~104°F)
	Storage: -15°C ~ +40°C (5°F ~104°F)
Recommended Operating Temperature Range	+74°F (23°C) to +80°F (27°C)
Self-Discharge	Less than 10% after 90 days, can be stored up to 6 months at 25°C (77°F); Fully recharging is required before usage, For higher temperatures the time interval will be shorter.

Charge Voltages		
Float Charging Voltage	13.5 to 13.8 VDC/unit@ (25°C)	
Equalization and Cycle Service Charging Voltage	14.3 to 14.5 VDC/unit @ (25°C)	
Maximum Charge Current(A)	40A	
Charging Temperature Compensation	Cycle use	-4mV/cell/°C
	Float use	-3mV/cell/°C

### BATTERY & TERMINAL DIMENSIONS (All units shown in mm)



Battery bank spacing required 12.5mm (1/2"inch) minimum



### Constant Current Discharge Rating Amperes @ 77°F (25°C)


Cut off voltage V/cell	15M	30M	45M	1H	2H	3H	5H	8H	10H	12H	20H
1.75V	220	140	103	85.3	45.2	34.0	25.6	17.3	14.20	12.26	8.0

**Note** The above data are average values, and can be obtained with 3 charge/discharge cycles. These are not minimum values.




# DC160-12 DATA SHEET


## Terminal Voltage(V) and Discharge Time




## Duration of discharge vs. Discharge current




## Percent Capacity vs. Temperature



## State of Charge(SOC) vs Open Circuit Voltage(OCV)



## Capacity Retention Characteristic



## Cycle Life vs. Depth of Discharge(DOD)

