8GTE35

SPECIFICATIONS

Nominal Voltage (V)	6V
Capacity at C/100	211 Ah
Capacity at C/20	196 Ah
Capacity at C/5	167 Ah
Weight	69 lbs. (31 kg)
Plate Alloy	Lead Calcium
Posts	Forged Bushings
Container/Cover	Polypropylene
Operating Temperature Range	-76°F (-60°C) - 140°F (60°C)
Charge Voltage @ 77°F (25°C)	
Cycle	6.9 - 7.3 volts
Float	6.7 - 6.8 volts
Vent	Self-sealing
Electrolyte	Sulfuric acid thixotropic gel
Terminal	S (SAE)

Rated UN2794 - Wet, Filled with Acid

Made in the U.S.A. by East Penn Manufacturing Co., Inc.

Distributed by:

Valve-Regulated, Gelled-Electrolyte Battery

DIMENSIONS

Inches (mm)

Length	**9.64 (245 mm)**
Width	**7.51 (191 mm)**
Height	**10.65 (270 mm)** *Including terminal*

Gel Cycle Life vs Depth of Discharge at +25°C (77°F)
Based on BCI 2-hour Capacity



baterias.com

MK Battery

1631 South Sinclair Street ● Anaheim, California 92806

Toll Free: 800-372-9253 ● Fax: 714-937-0818 ● E-mail: sales@mkbattery.com

All data subject to change without notice. No part of this document may be copied or reproduced, electronically or mechanically, without written permission from the company. ©2015 MK Battery