

JUMP STARTER PFP 12/24 1500

TECHNICAL CHARACTERISTICS

- Volts: 12V y 24V
- Battery: 2X45ah/ PC1100 HAWKER-ODYSSEY U.S.A.
- Amp. 12V start: 2200ah (5 sec.)
- Amp. 24V start: 1100ah (5 sec.)
- Amp. Máxi: 2450ah
- 2000ah Clamps
- 50mm flexible cable
- Polarity change warning
- Current surge protector
- Internal battery checker
- 2X Charger 3.6 a/h 5 stages
- Weight: 43kg
- Dimensions: Largo 400 mm, Ancho 300 mm, Alto 400mm
- Temperature: -40°C/+45°C



INSTRUCTIONS FOR USE AND SAFETY

BEFORE USING THE DEVICE FULLY CHARGE IT FOR 12H

- Firmly place the clamps on the terminals respecting the polarity and select the corresponding Anderson 12V or 24V socket.
- The LED lights will light up indicating the state of charge of the starter batteries and then start the vehicle.
- You can press the Test button to check the state of charge of the internal batteries.
- If the clamps have not been placed respecting the polarity, the starter beeps. In this case DO NOT select the appropriate Anderson socket without first changing to polarity.
- In diesel vehicles, wait for the heaters to act.
- Wait a few minutes with the engine running to allow the battery to partially recharge.
- This unit is equipped with an electronic surge voltage suppressor device.
- Use the supplied charger for optimal charging of the device. Always keep batteries charged.

WARRANTY

This device is guaranteed against manufacturing defects for 24 months from the invoice date, this will be proof of the guarantee and must be presented to examine any component of the device. The batteries must arrive with more than 12 volts since if it is lower not loaded properly. **ALL THE COMPONENTS OF THE STARTER CAN BE PURCHASED FROM YOUR REGULAR DEALER.**

**PFP 12/24-1500 SUITABLE FOR 100% OF 12V VEHICLES INCLUDED V6 DIESEL AND PETROL ENGINES AND V8-V10-V12 ENGINES.
SUITABLE FOR 100% 24V VEHICLES INCLUDING PUBLIC WORKS MACHINERY.**