

# **ODP-AGM75 86** (75/86-705)

# Technical Data Sheet

# **Battery Type**

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

### **Power & Performance**

Capacity (20-hour rate) 49Ah Capacity (10-hour rate) 45Ah	
Canacity (10 hour rate)  AFAb	
Capacity (10-hour rate) 45Ah	
Cold Cranking Amps (CCA, SAE J537) 708A	
PHCA - 5-second pulse current 1100A	
HCA 875A	
MCA 760A	
Reserve capacity 89 mins	5
Short circuit current (using IEC method) 2200A	
Internal resistance at 20°C (using IEC method) 2.8 m $\Omega$	

# **Dimensions & Weight**

Length	241 mm
Width	173 mm
Height (to top of terminals)	201 mm
Height Container	188 mm
Weight	19.7 kg

### **Temperature**

Operating Temperature Range	-40°C to +60°C
Optimum Storage Temperature	+20°C

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

# Charging & self-discharge

Type of charging curve	IUU
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

# Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

PDF Generated at https://eu.odysseybattery.com 16/11/2021 12:42:32 Information correct at time of exporting PDF. Please check website for updates.




EnerSysWorld Headquarters 2366Bernville Road Reading, PA 19605,USA Tel: +1-610-208-1991 / +1-800-538-3627


EH Europe GmbH Baarerstrasse 18 6300Zug.

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780

# **Terminal Position**



# **Terminal Type**





ODP-AGM75/86 LEFT POSITIVE **DUAL TERMINALS** (SAE & SIDE)

