

ODS-AGM40E (PC1100)

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

Voltage	12V
Capacity (20-hour rate)	45Ah
Capacity (10-hour rate)	43Ah
Cold Cranking Amps (CCA, SAE J537)	500A
PHCA - 5-second pulse current	1100A
HCA	800A
MCA	650A
Reserve capacity	87 mins
Short circuit current (using IEC method)	2450A
Internal resistance at 20°C (using IEC method)	$5.1~\text{m}\Omega$

Dimensions & Weight

9 mm
mm
6 mm
6 mm
.5 kg

Temperature

Operating Temperature Range	-40°C to +50°C
Optimum Storage Temperature	+20°C

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

Charging & self-discharge

Type of charging curve	100
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

PDF Generated at https://eu.odysseybattery.com 16/11/2021 12:49:20 Information correct at time of exporting PDF. Please check website for updates.




EnerSys World Headquarters 2366Bernville Road El Reading, PA 19605,USA B Tel: +1-610-208-1991 / +1-800-538-3627 Si

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300Zug, Switzerland

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780



Terminal Position



Terminal Type

