

# **ODS-AGM42L** (PC1200)

## **Technical Data Sheet**

## **Battery Type**

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

#### **Power & Performance**

Voltage	12V
Capacity (20-hour rate)	42Ah
Capacity (10-hour rate)	40Ah
Cold Cranking Amps (CCA, SAE J537)	540A
PHCA - 5-second pulse current	1200A
HCA	860A
MCA	725A
Reserve capacity	78 mins
Short circuit current (using IEC method)	2600A
Internal resistance at 20°C (using IEC method)	$4.5~\text{m}\Omega$



198 mm
165 mm
163 mm
170 mm
17.3 kg

## **Temperature**

Operating Temperature Range	-40°C to +50°C
Optimum Storage Temperature	+20°C

#### **Accreditations**

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

## Charging & self-discharge

Type of charging curve	100
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

## Fitting, handling & storage

Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).

PDF Generated at https://eu.odysseybattery.com 16/11/2021 12:49:15 Information correct at time of exporting PDF. Please check website for updates.




EnerSys World Headquarters 2366Bernville Road Reading, PA 19605,USA Tel: +1-610-208-1991 / +1-800-538-3627

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300 Zug, Switzerland

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780



### **Terminal Position**



# **Terminal Type**

