

MOTOBATT

QuadFlex™ Battery
 WWW.MOTOBATT.COM
 MBTX12U



Features

- Patented Quad Terminal Design - Reduce carrying costs
- 12V VRLA Hi Capacity Starting Battery
- Absorbed Glass Mat (AGM) technology
- Brass Terminals - superior conductivity
- US DOT, IATA certified non-spillable
- Highest AH Capacity in the Industry
- Factory Activated-Ready to Install

Performance Specifications

| | |
|---|---------------------------------------|
| Nominal Voltage ----- | 12 volts (6 cells) |
| Nominal Capacity | |
| 20-hr. (0.7A to 10.50 volts)----- | 14.4 AH |
| 10-hr. (1.4A to 10.50 volts)----- | 14.0 AH |
| 5-hr. (2.8A to 10.20 volts)----- | 11.9 AH |
| 1C. (14.0A to 9.6 volts)----- | 41Min (9.57AH) |
| 8C. (112A to 6.00 volts)----- | 3Min (5.6AH) |
| Approximate Weight ----- | 9.70 lbs. (4.40kg) |
| Energy Density (20-hr. rate) ----- | 1.66W-h/in ³ (101.2 W-h/l) |
| Specific Energy (20-hr. rate) ----- | 17.8W-h/lb (39.3 W-h/kg) |
| Internal Resistance (approx) ----- | 18 milliohms |
| CCA (-0.4°F/-18°C,7.2V,30S)----- | 200 amperes |
| CA (68°F/20°C,7.2V,30S)----- | 280 amperes |
| Shelf Life (% of nomomal capacityat 68°F (20°C)----- | SOC% OCV |
| 1 Months ----- | 97% 12.78V |
| 3 Months ----- | 91% 12.7V |
| 6 Months ----- | 83% 12.5V |


Operating Temperature Range

| | |
|-----------------|------------------------------|
| Charge ----- | -4°F(-20°C) to 122°F(50°C) |
| Discharge ----- | -40°F (-40°C) to 140°F(60°C) |

Case ----- ABS


Carton Contents -----1-MotoBatt MBTX12U Battery,
 Fit spacers (2 bottom),4 stainless steel terminal screws, 2 brass terminals, 4mm Allen Wrench, Install / user manual.

Brass Terminals (mm)



Terminal Screws: Stainless, M6 Thread
 Fastener: 4mm Allen Hex

Physical Dimensions: (in./mm)



L:5.94(151) W:3.43(87) H:5.12(130)
 TH.:5.71(145)

Tolerances are +/-0.04in.(+/-1mm) and +/-0.08in.(+/-2mm) for height dimensions.




RETAIL CARTON




C TERMINAL TERMINAL COVER SCREW WRENCH


Shelf life & Storage




Discharge Characteristics



Discharge Time vs. Discharge Current



Life Characteristics in Cyclic Use



Charging

Cycle Applications: limit initial current to 4.2A. Charge until battery voltage (under charge) reaches 14.8 to 15.0 volts at 68°F(20°C). Hold at 14.8 to 15.0 volts until current drops to under 280mA. Battery is fully charged under these conditions, and charger should be disconnected or switched to "float" voltage.

Note: Due to the self-discharge characteristics of this type of battery, it is imperative that they be charged within 6 months of storage, otherwise permanent loss of capacity might occur as a result of sulfation.

Chargers

MotoBatt offers a wide range of chargers suitable for batteries up to 4A. Please refer to the charger selection guide. Please contact our technical department for advice if you have difficulty in locating suitable models or contact us at www.motobatt.com.

Can be used to replace

| | | | |
|----------|---------|-----------|----------|
| YB12BB2 | YTX12BS | YTX14BS | YTX14HBS |
| YTX14LBS | KMX14BS | YTX15L-BS | |
| | | | |
| | | | |
| | | | |

Further Information

Please refer to our website www.motobatt.com to locate a distributor in your area.