Maintenance Free Motorcycle Batteries

WTZ5S-E

Specifications

Nominal Voltage(V)

12V

Nominal Capacity

10 hour rate	(0.4A	to	10.50V)	4Ah
5 hour rate	(0.68A	to	10.20V)	3.4Ah
1 C	(4A	to	9.60V)	1.8Ah
3 C	(12A	to	9.60V)	1.4Ah

Weight

Approx. 1.58kg(3.48Lbs.)

Internal Resistance (at 1KHz)

Approx. 16 mΩ

Cold Cranking Amperes (-17.8℃)

50A

High rate discharge characteristics (-10℃)

Discharge current (A)	30A
Duration (min)	1.8min
5 second voltage (V)	9.9V

Operating Temperature Range

Charge	-15℃(5℉)	to	40℃(104℉)
Discharge	-15℃(5℉)	to	50℃(122℉)
Storage	-15℃(5℉)	to	40℃(104℉)

Charge Retention (shelf life) at 20℃(68℉)

1 month	92%
3 month	90%
6 month	80%

Case Material

PP

Terminal Shape

Front	Side	Top
		

Dimensions

Length (L)	113+2-1 (4.45+0.08-0.04)
Width (W)	70+2-1 (2.76+0.08-0.04)
Height (H)	85+2-1 (3.35+0.08-0.04)
Overall Height (HT)	85+2-1 (3.35+0.08-0.04)

mm(inch)







290318-1D-V

LE LONG VIETNAM CO., LTD.

CÔNG TY TNHH LELONG VIỆT NAM

I 40 Bà Chánh Thâu, KP2, Thị Trấn Bến Lức Huyện Bến Lức, Tỉnh Long An TEL:+84-272-3872213 FAX:+84-272-3872350

II Cụm Công Nghiệp Đức Mỹ, Xã Đức Hòa Đông, Huyện Đức Hòa, Tỉnh Long An TEL:+84-272-3779666 FAX:+84-272-3779476

Contents in this data sheet are subject to change for improvement without prior notice to users. For clarifications and updated information, please contact us.