

ODYSSEY[®] BATTERY

ODP-AGM65 (65-760)

Technical Data Sheet

Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

Power & Performance

| | |
|--|----------|
| Voltage | 12V |
| Capacity (20-hour rate) | 64Ah |
| Capacity (10-hour rate) | 59Ah |
| Cold Cranking Amps (CCA, SAE J537) | 762A |
| PHCA - 5-second pulse current | 1500A |
| HCA | 1200A |
| MCA | 890A |
| Reserve capacity | 129 mins |
| Short circuit current (using IEC method) | 2500A |
| Internal resistance at 20°C (using IEC method) | 2.3 mΩ |

Dimensions & Weight

| | |
|------------------------------|---------|
| Length | 300 mm |
| Width | 183 mm |
| Height (to top of terminals) | 193 mm |
| Height Container | 173 mm |
| Weight | 22.6 kg |

Temperature

| | |
|-----------------------------|----------------|
| Operating Temperature Range | -40°C to +60°C |
| Optimum Storage Temperature | +20°C |

Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

Charging & self-discharge


| | |
|-----------------------------------|----------------|
| Type of charging curve | IUU |
| Charge voltage @+20°C | 14.4V to 14.8V |
| Self-discharge per month at +20°C | 1.25% |
| Self-discharge per month at +40°C | 5% |

Fitting, handling & storage



Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).





Terminal Position



Terminal Type



ODP-AGM65
LEFT POSITIVE
SAE TERMINALS



PDF Generated at <https://eu.odysseybattery.com> 16/11/2021 12:41:04
Information correct at time of exporting PDF. Please check website for updates.



EnerSys World Headquarters
2366 Bernville Road
Reading, PA 19605, USA
Tel: +1-610-208-1991 /
+1-800-538-3627

EnerSys EMEA
EH Europe GmbH
Baarerstrasse 18
6300 Zug,
Switzerland

EnerSys Asia
152 Beach Road
Gateway East Building #11-08
Singapore 189721
Tel: +65 6508 1780