# INCOMPARABLE DEEP CYCLE AGM BATTERY


LDC12-15 (12V15Ah)

LEOCH BATTERY




## CHARACTERISTICS

| Item | | Specifications |
|---|---|---|
| Voltage | | 12V |
| Dimension | Length | 151.5mm (5.96inches) |
| | Width | 99.5mm (3.92inches) |
| | Container Height | 98.0mm (3.86inches) |
| | Total Height | 98.2mm (3.87inches) |
| Approx Weight | | 3.95kg (8.71lbs) |
| Terminal | | T15-1(M5) |
| Container Material | | ABS |
| Capacity | 20HR | 15Ah |
| | 5HR | 13.5Ah |
| Operating Temp. Range | Discharge | -20~55°C (-4~131°F) |
| | Charge | 0~40°C (32~104°F) |
| | Storage | -15~40°C (5~104°F) |




## APPLICATIONS

- Electric scooter
- Electric wheelchair
- Electric toys
- Hospitals
- Warehouses
- ETC

carbon

AGM-GEL technology

Note: Terminal Torque Values in-lb(Nm):17.69-26.55(2.0-3.0)

# INCOMPARABLE DEEP CYCLE AGM BATTERY

LDC12-15 (12V15Ah)

LEOCH BATTERY

## GENERAL FEATURES

### Stable initial capacity

- PAM/NAM amount optimization
- 4BS crystal paste mixing & curing technology
- Double layer separator technology
- Improved design electrolyte S.G.

### Improved PSoC cycling

- Carbon boost technology
- Mix carbon boost technology
- Targeting for higher level through carbon technology

### Excellent deep cycle performance

- Plate assembly pressure re-engineering
- New PAM/NAM recipe introduced
- Gel electrolyte technology
- Rare earth alloy
- Double layer separator technology
- Lower acid filling temperature

### Less water loss

- PAM/NAM amount optimization
- New PAM/NAM recipe introduced
- Rare earth alloy

### Delay PAM softening and shedding

- Plate assembly pressure re-engineering
- 4BS crystal paste mixing & curing technology
- Higher paste density


### Solve NAM sulphation

- Carbon boost technology
- Pre-sulfate technology


### Optimize electrolyte stratification

- Introduce AGM-GEL technology


### Charging Profiles





### Relationship of OCV and State Of Charge




### Cycle Life in Relation to Depth Of Discharges




### Self-discharge Characteristics





**Leoch International Technology Ltd.**
www.leoch.com

**Leoch Batteries Pte Ltd**
www.leoch.sg

**Leoch Battery Corporation**
www.leochamericas.com

**Leoch Europe S.A.**
www.leoch.eu



Data above is recommended and the picture is only for battery effect display, Leoch reserve the final right of explanation.
© LEOCH. All rights reserved.Trademarks and logos are the property of LEOCH and its affiliates unless otherwise noted.Subject to revisions without prior notice. E&OE.



Publication No.:LB-LDC12-15-PD-EN-V1.2-20250816